



FLATPAK Cheat Sheet

Identifier Formats

ID

```
<ending>.<organization>.<name>
```

ID + architecture + branch

```
<ID>/<arch>/<branch>
```

ID + branch

```
<ID>//<branch>
```

ID + architecture

```
<ID>/<arch>//
```

Basic Commands

Install

```
$ flatpak install <remote> <ID>  
$ flatpak install <path-to-flatpakref>
```

Uninstall

```
$ flatpak uninstall <ID>
```

Run

```
$ flatpak run <ID>
```

Update

```
$ flatpak update
```

Search all remotes

```
$ flatpak search <term>
```

Remotes

List configured remotes

```
$ flatpak remotes
```

Add a remote

```
$ flatpak remote-add <remote-name> <URL>
```

Use `--if-not-exists` to avoid errors.

Remove a remote

```
$ flatpak remote-delete <remote-name>
```

List remote contents

```
$ flatpak remote-ls <remote-name>
```

Flatpak Builder

Command format

```
$ flatpak-builder <build-dir> <manifest>
```

Definitions

<build-dir>

Directory where build stuff happens

<manifest>

Path to the manifest file

Options

`--repo=<repo-name>`

Export to a specified repository

`--install`

Install the build result, if it succeeds

`--install-deps-from=<remote>`

Install build dependencies from a specified remote
